

ECE216 Course Summary

Basics

- * given $x(t)$ and you want to graph $y(t) = x(\alpha t + \beta)$
 - ↳ first apply time shift β
 - ↳ then scale t -axis by $\alpha \rightarrow \begin{cases} |\alpha| > 1: \text{horiz. "wider"} \\ |\alpha| < 1: \text{horiz. "squished"} \end{cases}$
(divide all t 's by α)
- * is $y(t) = x_1(t) + x_2(t)$ periodic and with what T_0 ?
 - ↳ yes if $\frac{T_1}{T_2} = \frac{l}{k}$ and l/k is rational
 - ↳ then $T_0 = lT_2 = kT_1 \Rightarrow T_0 = \text{LCM}(T_1, T_2)$
- * DT comp. expo. periodic iff ω is a rational multiple of 2π
 - ↳ $\omega_0 = k \frac{2\pi}{N_0} \leftarrow \omega_0$ must satisfy for smallest integer k


3. Fourier Series

- * Trigonometric FS: $x(t) = a_0 + \sum_{n=1}^{\infty} [a_n \cos(\omega_0 n t) + b_n \sin(\omega_0 n t)]$
$$a_0 = \frac{1}{T} \int_{-T/2}^{T/2} x(t) dt \quad a_n = \frac{2}{T} \int_{-T/2}^{T/2} x(t) \cos(\omega_0 n t) dt \quad b_n = \frac{2}{T} \int_{-T/2}^{T/2} x(t) \sin(\omega_0 n t) dt$$
- * CTFS v.s. DTFS (CTFS generally aperiodic, but DTFS is No-periodic)
 - $x(t)$ periodic $\left\{ \begin{array}{l} \rightarrow \text{CTFS represents } x(t) \text{ as infinite discrete sum of CT comp. exp.} \\ \rightarrow \text{DTFS " } x[n] \text{ " finite discrete sum of DT " " " } \end{array} \right.$
- * FS repr. of $x(t)$ is $x(t)$ repr. by sum of comp. exp. and lets us analyze frequency content of $x(t)$ by examining x_k

4. Fourier Transform

- * FT is extension of FS to aperiodic signals
- * idea: aperiodic signal is periodic signal with infinite period
- * $x(t) \xleftrightarrow{F} X(j\omega)$ called "FT" or "spectrum" of x
- * $u(t+a) - u(t-a) \xleftrightarrow{FT} \frac{2\sin(a\omega)}{\omega}$
- * $\frac{\sin(at)}{\pi t} \xleftrightarrow{FT} u(\omega+a) - u(\omega-a)$
- * if $x(t)$ very concentrated, $X(j\omega)$ very spread out
- * $x(t) = \sum_{k=-\infty}^{\infty} \alpha_k e^{jk\omega_0 t} \xleftrightarrow{FT} X(j\omega) = 2\pi \sum_{k=-\infty}^{\infty} \alpha_k \delta(\omega - k\omega_0)$
- * CTFT of a periodic signal is a sum of impulse functions located at multiples of the fundamental frequency ω_0
- * CTFT v.s. DTFT
 - CTFT represents aperiodic $x(t)$ as continuous sum of CT comp. exp. and in general is not periodic (spectrum)
 - DTFT " " " $x[n]$ " continuous sum of DT comp. exp. " " " is 2π -periodic (spectrum)
 - both $X(j\omega)$ and $X(e^{j\omega})$ capture the "amount" of frequency ω contained in x

5. Sampling, Aliasing, Interpolation

- * Sampling function: $s(t) = \sum_{n=-\infty}^{\infty} \delta(t - nT_s)$

- * Weighted sum of impulses: $s(t) x(t) = \sum_{n=-\infty}^{\infty} \delta(t - nT_s) x(t) = \sum_{n=-\infty}^{\infty} \delta(t - nT_s) x(nT_s)$
 $x_s(t)$ 2 sampled function
- * CTFS of sampling func.: $\omega_k = \frac{1}{T_s} \Rightarrow s(t) = \frac{1}{T_s} \sum_{k=-\infty}^{\infty} e^{jk\omega_s t}$
- * CTFT of sampling func.: $s(t) = \sum_{n=-\infty}^{\infty} \delta(t - nT_s) = \frac{1}{T_s} \sum_{k=-\infty}^{\infty} e^{jk\omega_s t} \xleftrightarrow{FT} S(j\omega) = \frac{2\pi}{T_s} \sum_{k=-\infty}^{\infty} \delta(\omega - k\omega_s)$
- * The CTFT of the sampling function is a sampling function!
 (impulse in t-dom spaced by T_s , in $j\omega$ -dom spaced by ω_s)
- * The spectrum of the sampled signal is a periodized version of spectrum of the original signal, with period ω_s in $j\omega$ -dom
- * $\omega_s \geq 2\omega_{max}$ or else will have aliasing (Nyquist Rate)

6. CT Systems

- * Linearity: it holds that $T\{\alpha x_1(t) + \beta x_2(t)\} = \alpha T\{x_1(t)\} + \beta T\{x_2(t)\}$
 - can apply superposition
 - input of 0 always results in 0
 - can apply to sums and integrals: $T\{\int \alpha x_1(t) dt\} = \alpha \int T\{x_1(t)\} dt$

* time invariance: if it holds that $y(t-a) = T\{x(t-a)\}$

→ to check, compute $y(t-a)$ and $T\{x(t-a)\}$ and check if they are equal → if yes, then T.I.

→ deals with only inputs and outputs (if you have say $y(t) = x(t) \cos t$, inputting $x(t-a)$ doesn't change $\cos t$... but shifting output does → ∴ not TI)

→ for integral systems, can apply change of variables

* Causality: if it holds that $y(t)$ only depends on past and present values of t (if future, then not causal)

→ if two inputs agree up to some time t_0 , then the corresponding outputs must also agree up to that time t_0 .

* memoryless: only the current time matters (not future or past)

→ derivative and RC ckt systems not memoryless

* invertibility: you can "undo" the operation of T

→ delay system invertible, but squaring system not

* BIBO stability: bounded inputs produce bounded outputs

→ to show system is not BIBO stable, find example bounded input that leads to unbounded output

* impulse response is system's response to a delta func. input

$$\rightarrow h(t) = T\{\delta(t)\}$$

$\rightarrow$ once $h(t)$ known, can compute $y(t)$ for any $x(t)$ input

* output of any LTI system given by:

$$y(t) = h(t) * x(t) = \int_{-\infty}^{\infty} h(t-\tau) x(\tau) d\tau$$

* a CT LTI system with $h(t)$ is

1) Causal iff $h(t) = 0$ for $\forall t < 0$

★ 2) Memoryless iff $h(t) = \alpha \delta(t)$ for $\alpha \in \mathbb{C}$

3) BIBO stable if h has finite action: $\int_{-\infty}^{\infty} |h(t)| dt < +\infty$

* changing order of series LTI systems still gives same result

* the inverse of an LTI sys. (if $\exists$ one) is also LTI sys. ($\delta * y = y$)

* the impulse response of parallel LTI's is $h_1(t) + h_2(t)$

* linear, inhomogeneous, constant-coefficient ODE's can define causal LTI systems.

$\rightarrow$ if we restrict ourselves to right-sided inputs $x(t)$ } then
 $\rightarrow$ " " " " " " " " solutions $y(t)$

$\rightarrow$ syst. is LTI and causal

$\rightarrow$ syst. is BIBO stable iff $\text{order}(\text{input}) \leq \text{order}(\text{LHS})$

and poles of transfer function (s -dom) have (-)ve real part

7. CT System Analysis with FT

* FT of impulse response $h(t)$ is $H(j\omega)$ frequency response

* LTI system with comp. exp. input: $x(t) = e^{j\omega_0 t}$

$$\rightarrow y(t) = H(j\omega)|_{\omega_0} \times e^{j\omega_0 t} = H(j\omega_0) e^{j\omega_0 t}$$

$\rightarrow$ due to eigenfunction property, LTI system amplitude-scales and phase-shifts any comp. exp. input

$\rightarrow$ meaning if input is comp. exp. then output is also comp. exp. with same frequency but scaled by $H(j\omega)$

* LTI response to periodic input: $x(t) = \sum_{k=-\infty}^{\infty} \alpha_k e^{jk\omega_0 t}$

$$\rightarrow y(t) = \sum_{k=-\infty}^{\infty} \alpha_k H(jk\omega_0) e^{jk\omega_0 t}$$


$\rightarrow$ if we know α_k of $x(t)$, we can get $X(j\omega)$ and we know $Y(j\omega) = X(j\omega) H(j\omega)$ and take IFT of that

$\rightarrow$ output $y(t)$ is $T_0 = \frac{2\pi}{\omega_0}$ periodic just like input

* convolution in t -dom means multiplication in $j\omega$ -dom

* An LTI system is invertible iff $H(j\omega) \neq 0$ for $\forall \omega \in \mathbb{R}$

* The above lets you find $H(j\omega)$ for feedback systems:



$$y = (x - y * h_2) * h_1$$

$$y = x * h_1 - y * h_2 * h_1$$

$$y + y * h_2 * h_1 = x * h_1$$

$$(\delta + h_2 * h_1) y = x * h_1$$


$$y = (\delta + h_2 * h_1)^{-1} x * h_1$$

$$\text{iff } (1 + H_2(j\omega) H_1(j\omega)) \neq 0$$


then

$$H(j\omega) = \frac{H_1(j\omega)}{1 + H_1(j\omega) H_2(j\omega)}$$


* The ideal LPF

$$h(t) = \frac{\sin(\omega_c t)}{\pi t}$$



$$\xleftrightarrow{\text{FT}}$$

$$H(j\omega) = \begin{cases} 1, & -\omega_c < \omega < \omega_c \\ 0, & \text{oth. } \omega. \end{cases}$$


* The ideal HPF

$$h(t) = \delta(t) - \frac{\sin(\omega_c t)}{\pi t}$$


$$\xleftrightarrow{\text{FT}}$$

$$H(j\omega) = \begin{cases} 1, & |\omega| > \omega_c \\ 0, & \text{oth. } \omega. \end{cases}$$


* Ideal non-causal filters v.s. non-ideal causal filters

→ ideal filter $h(t) \neq 0$ for $\forall t < 0$, so not causal and cannot be used for real-time application

→ ideal filters anticipate the input change (since not causal) and perfectly removes/rejects frequencies

→ non-ideal filters react only after input changes (since causal) and can only attenuate (not completely remove for eg.) signal

→ non-ideal: LPF, output @ $\angle$ and HPF, output @ $\angle$ → for RC ckt's

* FT method v.s. LT methods

→ FT: * 2-sided CTFT-able inputs

* causality not required

* used in signal processing...

→ LT: * LT-able inputs which are right-sided from time 0


* causal systems only

* used in control, energy, robotics, aerospace...

8. CT system Analysis with LT

- Laplace Transform defined if $x(t)$ is of exponential order/class and on a region of convergence (ROC)

$$X(s) = \int_{0^-}^{\infty} x(t) e^{-st} dt$$



- if LT ROC contains imaginary ($j\omega$) axis, the FT exists and can be found by subbing $s = j\omega$ into LT
- for causal BIBO systems, freq. response $H(j\omega)$ qualifies the steady-state

9. Fundamentals of DT systems

- properties from CT systems generally hold
- impulse response of summer: $h[n] = \sum_{k=-\infty}^n \delta[k] = \underline{u[n]}$ $n \geq 0$



Basics :

- continuous time signal (CT) : $x(t)$, $t \in \mathbb{R}$
- discrete time signal (DT) : $x[n]$, $n \in \mathbb{Z}$
- sampling : converting CT to DT
- interpolating : converting DT to CT
 - zero-order hold (ZOH)
 - first-order (FOH)

Operations :

- time shift : delays/advances in time $\rightarrow x(t \pm t_0)$ and $x[n \pm n_0]$
 - advance : shift signal to left to or n_0
 - delay : shift signal to right to or n_0
- time reversal : mirror signal about its vertical zero axis $\rightarrow x(-t)$ or $x[-n]$
- time scaling : horizontal (time scale) stretch or compression $\rightarrow x(at)$
 - horizontal "wide" : $|a| < 1 \rightarrow$ stretch
 - horizontal "squish" : $|a| > 1 \rightarrow$ compression
- periodic signal : if $x(t) = x(t+T) \rightarrow$ signal repeats itself after period of time
 - if I can find T s.t. $x(t) = x(t+T)$ for $\forall t$, then periodic, else aperiodic
- constant signal
 - DT case : periodic with $T_0 = 1$
 - CT case : periodic with undefined period
- sum/product of periodic signals periodic? $\rightarrow y(t) = x(t) + h(t)$

$\frac{T_1}{T_2} = \frac{k}{\ell}$

$\uparrow$
 T_0

$\uparrow$
 T_1

$\uparrow$
 T_2

} a rational number

 - then $T_0 = \text{LCM}(T_1, T_2)$ or : $T_0 = kT_1 = \ell T_2$




- **signal support** : where signal is not zero (active)
- **right-sided signal** : if for all $t < t_0$, signal is zero
- **finite duration signal** : non-zero over finite (bounded) interval
 - can turn finite duration signal into periodic signal
- **even signal** : $x(t) = x(-t)$
- **odd signal** : $x(-t) = -x(t)$
- **signal decomposition** : given any $x(t)$:

$$x_{\text{even}}(t) = \frac{x(t) + x(-t)}{2}$$

$$x_{\text{odd}}(t) = \frac{x(t) - x(-t)}{2}$$

- **signal amplitude**, $\|x\|_{\infty}$: peak value (absolute max) of signal
- **signal action**, $\|x\|_1$: the absolute area under the curve
- **signal energy**, $\|x\|_2^2$: the strength of the signal
- **impulse** : dirac delta function





$$\delta(t) = 0, t \neq 0$$

$$\int_{-\infty}^{\infty} \delta(t) dt = 1$$

$$\int_{0^-}^{0^+} \delta(t) dt = 1$$

$$\int_{-\infty}^{\infty} x(t) \delta(t-A) dt = x(A)$$

- **unit step** : heavyside function



Periodicity

$$\text{Euler's : } e^{j\theta} = \cos\theta + j\sin\theta$$

$$e^{-j\theta} = \cos\theta - j\sin\theta$$

$$\cos\theta = \frac{e^{j\theta} + e^{-j\theta}}{2}$$

$$\sin\theta = \frac{e^{j\theta} - e^{-j\theta}}{2j}$$



* DT complex exponentials only periodic iff ω is a rational multiple of 2π

$$\omega_0 = 2\pi \frac{K}{N_0} \leftarrow \omega_0 \text{ must satisfy for smallest integer } K$$

* DT complex exponentials are periodic functions of ω

$$e^{j(\omega+2\pi)n} = e^{j\omega n} e^{j2\pi n} = e^{j\omega n} \leftarrow \text{period } 2\pi$$

* Aliasing: when CT signal sampled $< 2f_{\max}$, called Nyquist frequency

* $\omega: 0 \rightarrow \pi$, increasing ω increases rate of oscillation

* $\omega: \pi \rightarrow$ fastest a signal can oscillate in DT

* $\omega: \pi \rightarrow 2\pi$, increasing ω lowers (slows) rate of oscillation

Fourier Series

* trigonometric FS: $x(t) = a_0 + \sum_{n=1}^{\infty} [a_n \cos(\omega_0 n t) + b_n \sin(\omega_0 n t)]$

average (DC)
Fourier coefficients
harmonics

$$a_0 = \frac{1}{T} \int_{-T/2}^{T/2} x(t) dt$$

$$a_n = \frac{2}{T} \int_{-T/2}^{T/2} x(t) \cos(\omega_0 n t) dt$$

$$b_n = \frac{2}{T} \int_{-T/2}^{T/2} x(t) \sin(\omega_0 n t) dt$$

* complex exponential FS: $x(t) = \sum_{k=-\infty}^{\infty} e^{jk\omega_0 t}$

Fourier coefficients

(complex numbers)

$$a_k = \frac{1}{T} \int_0^T x(t) e^{-jk\omega_0 t} dt$$

harmonic number

* orthogonality relations (if $m \neq n$)

$$\int_{-T/2}^{T/2} \sin(m\omega_0 t) \sin(n\omega_0 t) dt = 0$$

$$\int_{-T/2}^{T/2} \sin(m\omega_0 t) \cos(n\omega_0 t) dt = 0$$

$$\int_{-T/2}^{T/2} \cos(m\omega_0 t) \cos(n\omega_0 t) dt = 0$$



* Dirichlet Conditions

- 1) must be periodic
- 2) finite number of max and mins
- 3) finite number of discontinuities
- 4) absolutely integrable

* Convergence of FS

- 1) uniform convergence: FS converges to $x(t)$ everywhere consistently
- 2) point-wise convergence: FS converges to $x(t)$ at every point except possibly at discontinuities (FS converges to midpoint for finite dis.)

* Parseval's Relation : energy of signal per unit time (aka average power) is equal to energy of signal in frequency domain (sum of F.Coeff. energy)

* Tutorial 3 Notes

* odd function : $a_{-k} = -a_k \leftarrow x(-t) = -x(t)$

* imaginary function : $a_{-k} = -a_k^* \leftarrow x(-t) = -x^*(t)$

* $1 - 2\sin^2\theta = \cos 2\theta$

* $2\cos^2\theta - 1 = \cos 2\theta$

* Frequency = $\frac{k}{T}$

* given $z(t) = \alpha x(t) + \beta y(t) \rightarrow c_k = \alpha a_k + \beta b_k$

* given $x(t)$ and $y(t) = x(t - \tau) \rightarrow \beta_k = e^{-j\omega_0 \tau k} \cdot \alpha_k$

$\uparrow$ $\uparrow$
 α_k β_k